

TRIPLEXER



Electrical Specification			
Frequency Range, MHz	1710-1880	1920-2170	2300-2690
Insertion Loss, dB	< 0.4		
Return Loss, dB	< -18		
Isolation, dB	≥ 50 @ 1920-2170	≥ 50 @ 1710-1880	≥ 50 @ 1710-1880
	≥ 50 @ 2300-2690	≥ 50 @ 2300-2690	≥ 50 @ 1920-2170
3rd Order Inter Modulation (PIM), dBc	-130 / -150 / -160 @ (2 X 43 dBm)		
VSWR	≤ 1.25		
Impedance, Ω	50		
Max Power, Watts	100 (per port)		
Lightening Protection	DC Ground		
Mechanical Specification			
Connectors	DIN(F)		
Dimension, mm (subject to change)	198 x 190 x 50		
Weight, Kg (subject to change)	2.8		
Operating Temperature, °C	-30 to +70		
Humidity	5% - 95%		
Ports	Input Port: Three / Output Port: One		
Mounting Type	Wall / Pole Mount		

INTERNATIONAL SALES

536, Blenheim Centre, Hounslow, London
TW3 1ND, UK. Tel: +44-7787856914

INDIA HEADQUARTERS

D-213, Sector-63, Noida – 201301,
New Delhi NCR, India. Tel: +91-120-4859650